

THREE-CORNERED REC

The tarmac specification is as follows;

- Mark out location of 1.2m wide path by overall distance (Exact location to be agreed once awarded).
- Excavate in any material (Grass/soil) to formation level and cart materials away to licensed tip.
- Provide and lay 38x150mm tanalised timber edgings staked at 500mm. Centres. Stakes to be supplied 50mm x 50mm x 500mm tanalised and nailed into position.
- Lay weed-retaining membrane to base of footpath.
- Allow for grading off, preparing and rolling dtp. Type 1 stone to level 100mm thick.
- Provide, lay and roll 20mm nominal size dense bitumen macadam (BS.4987) as path base to a consolidated thickness of 40mm. Include for cutting all joints and painting with bitumen.
- Provide, lay and roll 10mm nominal size dense bitumen macadam (BS.4987) as wearing course to a consolidated thickness of 20mm. Include for cutting all joints and painting with bitumen.
- Grade upper ground level to a steady gradient, finishing flush with the path edge, prepare graded surface and seed with an amenity grade grass seed mix. Gradient to allow future grass maintenance and prevent from becoming an hazard.

Within your submission please provide a linear meterage for the works including disposal of spoil to a licenced tip and a separate price for retention of spoil on site (Minus disposal costs).